

▶ DPF 510GTR/MTR

Digital Print Pressure-Sensitive Vinyl Film

DPF 510GTR/MTR is a 100 microns monomeric film with a tinted, solvent-based pressure-sensitive removable adhesive. The two-sided polycoated liner provides excellent lay-flat properties. DPF 510 is available in a white gloss (DPF 510GTR) and white matte finish (DPF 510MTR). DPF 510 is rated for outdoor durability up to 3 years (unprinted). Printed durability is dependent on the ink system used.

APPLICATIONS & FEATURES

- Low tack adhesive is removable up to one year
- Short-term promotional and display graphics, including windows, decals, tradeshow, POP displays and interior floor graphics*
- Excellent printability on Eco-Solvent, Solvent and Latex print systems
- Ideal for interior and exterior applications on flat surfaces

**When used with Series 3510 Matte.*

PERFORMANCE & PHYSICAL DATA

PROPERTY	TEST METHODS	TYPICAL VALUE
SURFACE FINISH	Gloss Meter 60° Reflection	70 to 90 Gloss Units (Gloss) Up to 30 Gloss Units (Matte)
THICKNESS	Micrometer, Federal Bench Type	100 microns
TENSILE STRENGTH	Tensile Tester with 51 mm jaw separation; crosshead speed of 5.1 mm/s, web direction	≥ 1.8 kg/cm
ELONGATION	Instron Tensile Tester as above	≥ 200%
SHELF LIFE (IN BOX)	Ideal Storage Temperature 21°C and 50% relative humidity	1 year from factory shipment
APPLICATION TEMPERATURE RANGE	On clean, dry substrate	10°C to 32°C
SERVICE TEMPERATURE RANGE	On clean, dry substrate	-29°C to 65°C
DIMENSIONAL STABILITY	70°C, 48 hours	≥ 1.00mm
PEEL ADHESION	PSTC-1, 15 min, 21°C	≥ 0.09 kg/cm
LINER RELEASE	TLMI Release at 90°, 760 cm/min	21.7 g/cm

Standard Terms & Conditions Apply

USA

a 200 Boysenberry Lane, Placentia, CA 92870
p 800 232 7161 / +1 714 985 6300
f +1 714 985 6305

EUROPE

a Dr. Lelykade 22B, 2583CM Den Haag, The Netherlands
p +31 70 354 4311
f +31 70 355 7721

CHINA

a No. 1989 Xinchang Road, Weifang, Shandong, 262400
p +86 0536 6226568

FLOOR APPLICATIONS

DPF 510GTR/MTR is recommended for short-term interior floor applications such as smooth floors, sealed concrete, ceramic tile, waxed vinyl flooring, sealed wood, marble and terrazzo, when used with Series 3510 Matte, which is approved under the European Standard Certification EN 14041 for slip-resistance for Floor Graphic Materials. To determine the best product for application Arlon always recommends testing prior to using the above products on the actual surface as product performance can vary greatly depending on the surface type, level of foot traffic, elemental exposure and floor condition. Due to these variables, Arlon only warrants the material(s) for standard manufacturers defect and is unable to offer a warranty for the performance or clean removability of these products for floor graphic applications.

Please refer to Arlon's Installation Guide for detailed techniques and best practices.

EN 14041 - Resilient, textile and laminate floor coverings

Determination of the anti-slip properties (EN 14041) : Determination of the dynamic coefficient of friction of floor materials in accordance with EN 14041.

TERMS & CONDITIONS


The following is made in lieu of all warranties expressed or implied:

All statements, technical information and recommendations published by Arlon relating to Arlon products are based on tests believed to be reliable and within the accuracy of the equipment used to obtain the specific values. Their accuracy or completeness is not guaranteed and Arlon makes no warranty with regard thereto. Seller's and manufacturer's only responsibility shall be to replace any quantity of the product proved defective. Seller and manufacturer shall not be liable for injury, loss or damage, direct or consequential, arising out of use or the inability to use the product. Nor shall seller or manufacturer be liable for any costs or expenses incurred in the processing or printing on the product. Before using, user shall determine the suitability of the product for its intended use. User assumes all risk and liability of every nature in connection therewith. No statements or recommendations other than those contained in the technical information published by Arlon shall have force or effect unless contained in an agreement manually signed by the officers of seller and manufacturer.

June 2020

USA

 200 Boysenberry Lane, Placentia, CA 92870

 800 232 7161 / +1 714 985 6300

 +1 714 985 6305


EUROPE


 Dr. Lelykade 22B, 2583CM Den Haag, The Netherlands

 +31 70 354 4311

 +31 70 355 7721

CHINA

 No. 1989 Xinchang Road, Weifang, Shandong, 262400

 +86 0536 6226568